



PART NUMBER

PFF46-702G

DESCRIPTION

FRONT LOWER WISHBONE FRONT BUSH CAMBER ADJUSTABLE

INSTALLATION GUIDE

Product description:

This part polyurethane bush fits into the front position of the front lower wishbone to provide on car adjustment of camber to give +/- 0.5 degrees of adjustment. It is designed to complement PFF46-702G that fits into the rear position of the same arm to provide anti-lift and caster offset.

Contents (parts per pack):

2 x A Part Polyurethane bushes

2 x Stainless steel sleeves

1 x PTFE / Silicone Bush Assembly Grease

2 x B Part Polyurethane bushes

1 x C spanner

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a guide and in conjunction with workshop manual.

It is recommended that:

-all work to be carried out by a licensed technician;

-all safety precautions adhered to;

-wheel alignment to be checked and adjusted as required after any suspension work.

All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

1. Remove original bush from the wishbone, clean any dirt and corrosion from the bore in the arm. Using file remove any sharp edges from the bore of the arm.
2. Push the thicker A part polyurethane bush into the arm from the front of the car.
3. Push the thinner B part polyurethane bush into the arm from the rear of the car.
4. Apply the supplied PTFE / Silicone grease to the bore and end faces of each bush and insert the stainless steel sleeve into each bush.
5. Re-fit the arm to the car and tension all hardware to manufacturers recommended torque settings.
6. Test drive the vehicle and perform full wheel alignment check and adjustment. To adjust camber, loosen front bush mounting bolt to free the bush and rotate the sleeve using the supplied spanner to achieve desired camber angles. For maximum negative camber, position the bore of the sleeve towards the middle of the car.

