

PFF5-301

FRONT ARM REAR BUSH

INSTALLATION GUIDE

Product description:

PFF5-301 - FRONT ARM REAR BUSH

Contents (parts per pack):

- 2 x purple outer bushes
- 2 x black inner bushes
- 2 x metal washers
- 1 x grease

Please read the complete fitting instructions and check package components before fitment. These fitting instructions are to be used as a quide and in conjunction with workshop manual. It is recommended that:

- all work to be carried out by a licensed technician;
- all safety precautions adhered to;
- wheel alignment to be checked and adjusted as required after any suspension work. All fasteners must be tensioned to manufacturer's torque settings.

Fitting Instructions:

- 1. Remove front arm from the car, remove original rear bush from arm, remove original bush from bracket.
- 2. Lightly roughen the bore of the bracket and the pin on the arm with emery cloth.
- 3. Push the purple outer bush into the bracket with the larger diameter facing the front of the car and the arm.
- 4. Place the washer onto the pin of the arm then push the black inner bush onto the pin of the arm making sure it is pushed all the way on.
- 5. Lubricate the bore of the purple bush and the outside of the black bush.
- 6. Push the bracket and purple bush onto the black bush on the arm, the black bush will fit all the way into the recess on the purple bush.
- 7. Refit the arm to the car, road test and check and adjust wheel alignment





